REFERENCE DETAIL:

HI-PERF RIDGE VENT

SLOPE TO SLOPE, SHINGLED VERSION

Z BRACKET, INTERMITTENT SPACERS AND EXPANDED METAL SUPPORT SCREEN ARE ALL FACTORY ASSEMBLED

ALL FASTENERS A 8" WIDE — SEALANT BY OTH COVER PLATE		THE RIDGE OPENING MAY BE PROVIDED BY ONE OF TWO METHODS: 1. THE ACTUAL KNOWN
AT EACH JOINT INTERMITTENT SPACER 12" O.C. .050 EXPANDED METAL SUPPORT SCREEN 7/16" HEM 3/2" WIDE DEFLECTOR BAFFLE AT DEFLECTOR JOINTS DEFLECTOR (12'-0" LENGTHS TYP. BOTH SIDES) (ONLY REQUIRED IF PITCH IS LESS THAN 4 / 12)	STYLE A STYLE B RIDGEVENT COVER	RIDGE OR NFA
	CONTINUOUS 20 GA. GALV. Z BRACKET EXISTING SLUNCLED BOOF	OR 2. FIELD OR PLAN CONDITION MEASUREMENTS: ACTUAL LINEAL FOOTAGE OF RIDGE VENTILATION TYPE: VENTED NAILBASE AIR SPACE DIMENSION OF VENTED NAILBASE OR
	(ANYTHING LESS THAN A 4 / 12 PITCH REQUIRES DEFLECTORS) ROOF PITCH	ATTIC ATTIC FLOOR SQUARE FOOTAGE RIDGE BEAM WIDTH IF APPLICABLE
Fabrication will proceed only after receipt of signed print approval.	COVER MATERIAL:	QUANTITIES:
Print Approval: Architect and/or contractor shall verify all dimensions, sizes and quantities. All products to be installed in strict accordance with Metal-Era's printed instructions.	☐ 24 GA. GALV. STEEL ☐ .040" ALUI ☐ .050" ALUMINUM ☐ .063" ALUI	
Approved by:	OTHER FINISH:	STYLE ASTYLE B
PROJECT: ARCHITECT:		Phone: 800-558-2162 Fax: 800-770-3934 www.metalera.com
CONTRACTOR:		DATE: 08/01/17 SHT.# OF
REPRESENTATIVE:		DRN BY: JAB CKD BY: SAK DWG# 31024-19109